




Automatic Finisher Series **AFR-24S**



Optimizing your sheetfed solution

GCC AFR-24S enables the optimized process with versatile capability for short run production that simplify your operation through an automatic working procedure in sampling, folding carton packaging, custom cards, labels and stickers.



Media Loading



Mark Detecting



Creasing & Cutting



Media Collecting

Feature

- Creasing tool
- Support media standard up to B2 size
- Media Stacking Up to 50mm (250 sheets)
- 4 suction cups to move the sheet easily
- Adjustable Media Tray
- AAS II with contour cutting
- Multiple parameter setting by 16 different colors
- Media Separation Mechanism to avoid paper jam



Package



Sticker



Sticker



Card

Specification

Model	AFR-24S
Supported media size	A4 (297 x 210 mm), SRA4 (320 x 235 mm), A3 (297 x 420 mm), SRA3 (320 x 450 mm), B3 (500 x 353 mm) (landscape orientation) Optional: B2 (500 x 707 mm) A3+ (329 x 483 mm) (portrait orientation)
Interface	USB 2.0 (Full Speed), Serial (RS-232C) and Ethernet
Power source	100 to 240 V AC (It is required three-prong outlet.)
Operating environment	Temperature: 15 to 30°C/60°F~86°F Humidity: 25 to 75 % RH (non-condensing)
Dimensions	Approx. 1098(W) x 1140 (D) x 782 (H) mm
Weight	Approx. 47.5 kg (Cutter unit: 25.5 kg, Auto feeder unit: 22 kg)
Cutter Unit	RX II-61 (Creasing)
Cutting speed	Max. 1,530 mm/s (at 45° direction)
Acceleration	Max. 4.2 G
Cutting force	Max. 600 g
Interface	USB 2.0 (Full Speed), Serial (RS-232C) and Ethernet
Power source	100 to 240 V AC
Power consumption	Max. 251.8 watts
Auto Feeder Unit	Auto Feeder
Supported media	Width: 279 to 500 mm, Length: 210 to 700 mm (Extend to 700 mm length when the optional extension table is installed.) Up to 350 g/m ²
Capacity of supply tray	250 Sheets @150 g/m ² or up to 50 mm height (It varies by the material, thickness and condition of media.)
Interface	Serial (RS-232C)
Power source	AC adapter, 100 to 240 V AC, Approx. 60 VA at output power

